

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/003672 A1

BEST AVAILABLE COPY

(51) International Patent Classification:

F41A 9/43

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NL, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/IB2004/051062

(22) International Filing Date: 30 June 2004 (30.06.2004)

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data:

2003/5146 2 July 2003 (02.07.2003) ZA


(71) Applicant (for all designated States except US): DENEL (PTY) LTD [ZA/ZA]; 368 Selbourne Avenue, Centurion, 0182 Pretoria (ZA).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AMMUNITION LOADING ASSEMBLY



(57) Abstract: This invention relates to an ammunition loading assembly (10) for loading a projectile (12) into a barrel (14) of a gun comprising an urging member (16) for urging the projectile (12) into the said barrel (14). The assembly (10) further includes a drive means (18) for driving the urging member (16) between a projectile receiving position outside the barrel (14) and a projectile delivery position inside the chamber (20) of the gun. The drive means (18) includes a drive chain assembly (22), for driving the urging member (16) between the projectile receiving and delivery positions. The drive chain assembly (22) is rigid in all directions but one, the arrangement being such that the drive chain assembly (22) pushes the urging member (16) from the projectile receiving position to the projectile delivery position and pulls the urging member (16) from the projectile delivery position to the projectile receiving position. The assembly further includes first and second chain-retaining devices (42, 44) for limiting curving of the chain assembly and guiding the chain when moving out of the magazine.

WO 2005/003672 A1